



FLYWEIGHT GOLD

Premium Grade Lightweight Body Filler Title

Description	<p>FLYWEIGHT GOLD is a two component polyester filler paste used for the filling of holes and imperfections in most substrates.</p> <p>The FLYWEIGHT GOLD formulation uses sophisticated lightweight technology to produce excellent filling properties combined with smooth application and very easy sanding. It has been designed with the most challenging professional applications in mind.</p>
Health and Safety Statement	<p><u>FOR PROFESSIONAL USE ONLY</u>. Read full instructions before use.</p> <p>IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.</p> <p>U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.</p>
Surface preparation and instructions for use	<p>FLYWEIGHT GOLD polyester filler can be used on the following surfaces:-</p> <ul style="list-style-type: none">• Bare metal – e.g. Steel, degrease and abrade with P80 paper.• Original paint surfaces (with the exception of thermoplastic acrylics) – degrease and abrade with P180 grit paper.• GRP – degrease and abrade with P80 grit paper.
Application and storage information	<p>100 parts by weight FLYWEIGHT GOLD polyester filler, 2 parts by weight U-POL hardener for polyester filler.</p> <p>The exact mixing ratio is not critical, although over or under catalyzation may affect the gel time. Do not greatly over catalyze the paste as this will not significantly speed up the gel time and could lead to bleed through and bleaching problems when over-painting later. Staining may also occur where too little hardener is used.</p>
Pot Life	Once mixed, 4-5 mins. at 20°C with 2% hardener.
Tools	Mixing board, filler knife, plastic or rubber spatula
Drying Time	Sandable after 15 mins. at 20°C. IMPORTANT – This fillers is very easy to sand and therefore recommend that nothing coarser or lower than P80 paper is used.
Over Painting	FLYWEIGHT GOLD polyester filler can be over-painted with most paint systems including 2K.
Product Codes	FLYG/3 - 3L tin
VOC Information	The EU limit for this product (product category: IIBb) in ready to use form is 250g/litre. The VOC content of this product in ready to use form is 100g/litre

U-POL, 1 TOTTERIDGE LANE, WHETSTONE, LONDON, N20 0EY, UK
Home Sales T: +44(0)870 899 8200; F:+44(0)870 899 8211; E: sales@u-pol.com;
Export Sales T: +44(0)870 899 8200; F:+44(0)870 899 8299; E: exportsales@u-pol.com;
Technical T: +44(0)870 899 8310; F:+44(0)870 899 8351; E: technicaldepartment@u-pol.com;
WEBSITE: WWW.U-POL.COM